## Weighbeams Mild Steel - R420-Industrial Indicator

Capacity 3000kg x 0.5kg graduation with a high Accuracy Scale 0.1% of the applied load The Euroscales Weighbeams are designed for portability and can be re-sited and up and running again in minutes. Their low profile design make them especially easy to load by manual hand pallet trucks. The R420 indicator is a comprehensive general purpose indicator designed with both the installer and operator in mind.

Flexibility is the key with its award winning modular accessory design. Modules include: additional serial options, input/outputs, analogue outputs, external buttons and battery or AC option. The robust input/output has been designed for direct connection into PLC's. Powerful product configuration allows for parameters like setpoint targets, piece weights and units conversions to be stored for each product. Simple setup through a menu system, either directly using the alpha numeric keypad or through our Viewer programme on a PC. Operator friendly, with a large two line display using logical prompts, and dedicated and programmable function keys. Printing can be tailored with custom record, docket or reports printouts. Applications: Weighbridges, Floor scales, Goods receiving and shipping, Parts counting, Silo weighing and Process control.



Performance	
Resolution	100,000 div @ 0.25 μV/Div
Excitation	7.4V DC
Drive	16 x 350 ohm
Linearisation	10 points
Range	Single/Dual Range, Dual Interval
Approvals	EU OIML R76, 10,000 Divs. @ 0.7μV/Div / C-Tick, CE & FCC
Physical	
Display Type	LCD display; LED backlight Housing ABS Plastic IP65
Digit Size	29mm Primary,18mm SecondaryDimensions246(W) x 121(H)

Keypad	23 Silicon Keys	Pack Weight	0.70 kg
Power Switch	Front Panel with Memory	Function Keys	3 Fixed, 3 Progr
Power input Plug top AC AC Battery Features	12-24 VDC 110-240 VAC (Acc) mains s 12V 2.5Ah NiMH (Acc) rech		
Serial 1A	RS232	Serial 1B	RS485 TX Only
Accessory Slots	4	Input / Output	32 I/O
Set Points	8		
Functions	R420-K401—1 Product		
R420-K402—250 Produ	cts Counting with Piece Weig	iht Entry,	
Clock Calendar, 4/6 Wir	eCustom Unit Switching, Hol	d & Peak Hold, Custom Print	ing, Auto Output
Optional extra Serial Po	rts		
Optional Analogue Outp	put		
Weighbeams			
Loadcells	IP67 sealed stainless steel	load cells—Flintec	
Standard Finish	Smooth steel finish / high q	uality paint finish in blue grey	RAL 7031
Construction	Heavy duty folded mild stee	l construction	
Size	1200mm long + handle, wid	th 120mm, height 60mm	

- -

Cables	standard cables 2.5M length with Amphenol plugs
Warranty	12 Months on loadcells
Feet	Weights and Measures certified loadcell mounts, passive zinc plated