Weighbeams Stainless Steel - MT IND226x Atex Zones 1, 21, 2 and 22

Capacity 3000kg x 0.5kg graduation with a high Accuracy Scale 0.1% of the applied load The Euroscales Weighbeams are designed for portability and can be re-sited and up and running again in minutes.

Their low profile design make them especially easy to load by manual hand pallet trucks. The MT IND226x is designed for simple weighing applications in hazardous areas, it has three available power sources: an external battery, 230v Power supply unit and 120v Power supply unit.



Performance

Resolution	Max 30,000 divisions, weighing ranges : single range	
Keypad	Hardcoated polyester overlay, 6 keys, tactile-feel	
[II		
Housing		
Full stainless steel enclosure 220mm (w) x 148mm (d) x 132mm (h)		
Protection		
IP66 dust and water ingress rating		

Hazardous Rating

ATEX: II 2 G EEx ib IIC T4 (Gas), II 2 D Ex tD A21 IP66 T60°C (Dust)

Digital

Display	7-segmented LED, 6 Digit, 30mm high
Power Input External Battery	Stainless steel housing, NIMH cells 8Ah, includes 3m cable
230 Mains Supply	230 VAC Power supply unit
120 Mains supply	120 VAC Power supply unit
Weighbeams Loadcells	IP67 sealed stainless steel load cells - Flintec
Standard finish	Brushed 160 grit stainless steel finish
Construction	Heavy duty folded stainless steel construction
Size	1200mm long + handle, width 120mm, height 60mm
Cables	Standard cables 2.5M length with Amphenol plugs
Warranty	12 Months on loadcells
Feet	Weights and Measures certified loadcell mounts, stainless steel